



Dell Networking S4810

High-performance 10/40GbE top-of-rack switch

High-density, 1RU 48-port 10GbE switch with four 40GbE uplinks and ultra-low-latency, non-blocking performance to ensure line-rate performance; complete with feature-rich Dell Networking OS and storage optimization for iSCSI, FCoE transit and DCB.

Ultra-low-latency, data center optimized

The Dell Networking S-Series S4810 is an ultra-low-latency 10/40GbE top-of-rack (ToR) switch purpose-built for applications in high-performance data center and computing environments. Leveraging a non-blocking, cut-through switching architecture, the S4810 delivers line-rate L2 and L3 forwarding capacity with ultra low latency to maximize network performance. The compact S4810 design provides 48 dual-speed 1/10GbE (SFP+) ports as well as four 40GbE QSFP+ uplinks to conserve valuable rack space and simplify the migration to 40Gbps in the data center core. Priority-based flow control (PFC), data center bridge exchange (DCBX) and enhance transmission selection (ETS), coupled with ultra low latency and line rate throughput, make the S4810 ideally suited for iSCSI storage, FCoE transit and DCB environments. In addition, the S4810 incorporates multiple architectural features that optimize data center network flexibility, efficiency and availability, including I/O panel to PSU airflow or PSU to I/O panel airflow for hot/cold aisle environments, and redundant, hot-swappable power supplies and fans.

The S4810 also supports Dell Networking's Open Automation Framework, which provides advanced network automation and virtualization capabilities for virtual data center environments.

An Active Fabric™ design with S4810 switches can be built out to create scalable, high-performance 10/40GbE data center networks. The resiliency of an Active Fabric is superior to legacy, centralized core architectures, since the failure of a single node within a CLOS network cannot bring down the entire switching fabric.

The S4810 is supported with Active Fabric Manager (AFM), which helps automate design and deployment of multi-tier fabrics. AFM helps customers manage multiple fabrics from a single console, enabling a unified view of the entire fabric, when combined with Dell OMNM and other management solutions. With AFM, over 25 templates can be customized for specific workload and deployment scenarios, easily delivering active/active L2 or L3 designs for 1/10/40G with Dell Z9000 to rack and blade infrastructures (including Dell MXL).

Key applications

- High-density 10GbE ToR server aggregation in high-performance data center environments
- Design with the Z-Series fabric core switch to create a flat, two-tier, non-blocking 1/10/40GbE data center network design
- Design a Clos-based Active Fabric with Z9000 switch in leaf and spine with the S4810/S4820T 10GbE ToR switches for cost-effective aggregation of 10GbE uplinks
- Enterprise iSCSI (iSCSI over DCB)

Key features

- 1RU high-density 10/40GbE ToR switch with 48 dual-speed 1/10GbE (SFP+) ports and four 40GbE (QSFP+) uplinks (totaling 64 10GbE ports with breakout cables)
- 1.28Tbps (full-duplex) non-blocking, cut-through switching fabric delivers line-rate performance under full load with 800ns latency
- Scalable L2 and L3 Ethernet switching with QoS and a full complement of standards-based IPv4 and IPv6 features
- VLT and eVLT: multi-chassis link to enable up to 576 10GE (3:1 over subscription)
- User port stacking support for up to six units
- Open Automation Framework adds VM awareness as well as automated configuration and provisioning capabilities to simplify the management of virtual network environments
- Modular Dell Networking OS software delivers inherent stability as well as advanced monitoring and serviceability functions
- Redundant, hot-swappable power supplies and fans
- Hardware support for DCB, FIPS operation

Ultra-low-latency
10GbE top-of-rack
switch optimized for
data center efficiency.

Specifications: S4810 high-performance 10/40-GbE top-of-rack switch

Dell SKU description

S4810

S4810, 48x 10GbE SFP+, 4x QSFP+, 1x AC PSU, 2x Fans, I/O Panel to PSU Airflow
 S4810, 48x 10GbE SFP+, 4x QSFP+, 1x AC PSU, 2x Fans, PSU to I/O Panel Airflow
 S4810, 48x 10GbE SFP+, 4x QSFP+, 1x AC PSU, 2x Fans, PSU to I/O Panel Airflow, Rear Mnt Bracket
 S4810, 48x 10GbE SFP+, 4x QSFP+, 1x DC PSU, 2x Fans, I/O Panel to PSU Airflow
 S4810, 48x 10GbE SFP+, 4x QSFP+, 1x DC PSU, 2x Fans, PSU to I/O Panel Airflow
 S4810, 48x 10GbE SFP+, 4x QSFP+, 1x AC PSU, 2x Fans, I/O panel to PSU Airflow (Normal), TAA/FIPS/USGv6-L2
 S4810, 48x 10GbE SFP+, 4x QSFP+, 1x AC PSU, 2x Fans, PSU to I/O Panel Airflow (Reverse), TAA/FIPS/USGv6-L2
 S4810, 48x 10GbE SFP+, 4x QSFP+, 1x AC PSU, 2x Fans, I/O Panel to PSU (Normal) Airflow, TAA/FIPS/USGv6-L2
 S4810, 48x 10GbE SFP+, 4x QSFP+, 1x AC PSU, 2x Fans, PSU to I/O Panel (Reverse) Airflow, TAA/FIPS/USGv6-L2

Redundant power supplies

S4810, AC Power Supply, I/O Panel to PSU Airflow
 S4810, AC Power Supply, PSU to I/O Panel Airflow
 S4810, DC Power Supply, I/O Panel to PSU Airflow
 S4810, DC Power Supply, PSU to I/O Panel Airflow

Fans

S4810 Fan Module, I/O Panel to PSU Airflow
 S4810 Fan Module, PSU to I/O SR4 Panel Airflow

Optics

Transceiver, QSFP+, 40GbE SR Optics, 850nm Wavelength, 100–150m Reach on OM3/OM4
 Transceiver, QSFP+, 40GbE eSR Optics, 850nm Wavelength, 300–400m Reach on OM3/OM4
 Transceiver, SFP+, 10GbE, SR, 850nm Wavelength, 300m Reach
 Transceiver, SFP+, 10GbE, LR, 1310nm Wavelength, 10km Reach
 Transceiver, SFP+, 10GbE, DWDM, ITU Channel 17–61, 40km Reach
 Transceiver, SFP+, 10GbE, ER, 1310nm Wavelength, 40km Reach
 Transceiver, SFP+ LRM (Long Reach Multimode) Optic, 10GbE, 1310nm Wavelength, 220m Reach on MMF
 Transceiver, SFP, 1000Base-SX, 850nm Wavelength, 550m Reach
 Transceiver, SFP, 1000Base-LX, 1310nm Wavelength, 10km Reach
 Transceiver, SFP, 1000Base-T

Cables

Cable, 40GbE QSFP+ to 4xSFP+, Direct Attach Breakout Cable, 0.5m, 1m, 3m, 5m, 7m
 Cable, 40GbE QSFP+, Active Fiber Optic, 10m, 50m
 Cable, 40GbE QSFP+, Direct Attach Cable, 0.5m, 1m, 3m, 5m, 7m
 Cable, 40GbE MTP to 4xLC, 1m, 3m, 5m, 7m Optical Breakout Cable (optics not included)
 Cable, 40GbE MTP Fiber over OM3, 1m, 3m, 5m, 7m, 10m, 25m, 50m (75m and 100m in 2014)
 Cable, SFP+, CU, 10GbE, Direct Attach Cable, 0.5m, 1m, 3m, 5m, 7m

Software

Software, FTOS: Networking Operating System Software, S4810
 Software, Networking, iSCSI-Optimized Configuration, S4810
 Software, Networking, FCOE-Optimized Configuration, S4810

Note: In-field change of airflow direction not supported.

Physical

48 line-rate 10 Gigabit Ethernet SFP+ ports
 4 line-rate 40 Gigabit Ethernet QSFP+ ports
 1 RJ45 console/management port with RS232 signaling
 Size: 1 RU, 1.73 x 17.32 x 18.11" (4.4 x 44 x 46 cm) (H x W x D)
 Weight: 14.39 lbs (6.54 kg)
 ISO 7779 A-weighted sound pressure level: 59.6 dBA at 73.4°F (23°C)
 Power supply: 100–240V AC 50/60Hz
 Max. thermal output: 1194 BTU/h
 Max. current draw per system:
 4A at 100/120V AC 2A at 200/240V AC
 10A at 36V DC 5A at 72V DC
 Max. power consumption: 350 Watts (AC), 300 Watts (DC)
 Typ. power consumption: 220 Watts
 Max. operating specifications:
 Operating temperature: 32°F to 104°F (0°C to 40°C)
 Operating humidity: 10 to 85% (RH), non-condensing
 Max. non-operating specifications:
 Storage temperature: –40°F to 158°F (–40°C to 70°C)
 Storage humidity: 5 to 95% (RH), non-condensing

Redundancy

Hot swappable redundant power
 Hot swappable redundant fans

Performance

MAC addresses: 128K
 IPv4 routes: 16K
 IPv6 routes: 8K (shared CAM space with IPv4)
 Switch fabric capacity: 1.28Tbps (full-duplex)
 640Gbps (half-duplex)
 Forwarding capacity: 960Mpps
 Link aggregation: 8 links per group, 128 groups per stack
 Queues per port: 4 queues

Layer 2 VLANs: 4K
 MSTP : 64 instances
 Line-rate layer 2 switching: All protocols, including IPv4 and IPv6
 Line-rate layer 3 routing: IPv4 and IPv6
 IPv4 host table size: 8K
 IPv6 host table size: 4K
 IPv4 multicast table size: 4K
 LAG load balancing: Based on Layer 2, IPv4 or IPv6 headers
 Sub 700ns
 Latency: 9MB
 Packet buffer memory: 2GB
 CPU memory:

IEEE compliance

802.1AB LLDP
 802.1ag Connectivity Fault Management
 802.1D Bridging, STP
 802.1p L2 Prioritization
 802.1Q VLAN Tagging, Double VLAN Tagging, GVRP
 802.1s MSTP
 802.1w RSTP
 802.1X Network Access Control
 802.3ab Gigabit Ethernet (1000BASE-T)
 802.3ac Frame Extensions for VLAN Tagging
 802.3ad Link Aggregation with LACP
 802.3ae 10 Gigabit Ethernet (10GBASE-X)
 802.3ba 40 Gigabit Ethernet (40GBASE-SR4, 40GBASE-CR4) on Optical Ports
 802.3u Fast Ethernet (100BASE-TX) on Management Ports
 802.3x Flow Control
 802.3z Gigabit Ethernet (1000BASE-X)
 ANSI/TIA-1057 LLDP-MED
 Force10 PVST+
 MTU 12,000 bytes

RFC and I-D compliance

General Internet protocols

768	UDP	1350	TFTP
793	TCP	2474	Differentiated Services
854	Telnet		
959	FTP	3164	Syslog
1321	MD5	5880	BFD

General IPv4 protocols

791	IPv4	1812	Routers
792	ICMP	1858	IP Fragment Filtering
826	ARP	2131	DHCP (relay)
1027	Proxy ARP	2338	VRRP
1035	DNS (client)	3021	31-bit Prefixes
1042	Ethernet Transmission	3046	DHCP Option 82
1305	NTPv3	3069	Private VLAN
1519	CIDR	3128	Tiny Fragment Attack Protection
1542	BOOTP (relay)		

General IPv6 protocols

2460	IPv6	1858	IP Fragment Filtering
2461	Neighbor Discovery (partial)	2675	Jumbograms
		3587	Global Unicast Address Format
2462	Stateless Address Autoconfiguration (partial)	4291	Addressing
2463	ICMPv6		

RIP

1058	RIPv1	2453	RIPv2
------	-------	------	-------

OSPF

2154	MD5	3623	Graceful Restart
1587	NSSA	4222	Prioritization and Congestion Avoidance
2328	OSPFv2		
2370	Opaque LSA		

BGP

1997	Communities		
2385	MD5		
RFC 2545	BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing		
2439	Route Flap Damping		
2796	Route Reflection		
2842	Capabilities		
2858	Multiprotocol Extensions		
2918	Route Refresh		
3065	Confederations		
4360	Extended Communities		
4893	4-byte ASN		
5396	4-byte ASN representations		
draft-ietf-idr-bgp4-20	BGPv4		
draft-ietf-idr-restart-06	Graceful Restart		
draft-michaelsen-4byte-as-representation-05	4-byte ASN Representation (partial)		

IS-IS

RFC 1195 Routing IPv4 with IS-IS
 RFC 5308 Routing IPv6 with IS-IS

Multicast

1112	IGMPv1	3569	SSM for IPv4
2236	IGMPv2	4541	IGMPv1/v2 Snooping
3376	IGMPv3		
draft-ietf-pim-sm-v2-new-05	PIM-SM		

Network management

1155	SMv1		
1156	Internet MIB		
1157	SNMPv1		
1212	Concise MIB Definitions		
1215	SNMP Traps		
1493	Bridges MIB		
1850	OSPFv2 MIB		
1901	Community-based SNMPv2		
2011	IP MIB		
2012	TCP MIB		
2013	UDP MIB		
2096	IP Forwarding Table MIB		
2570	SNMPv3		
2571	Management Frameworks		
2572	Message Processing and Dispatching		
2576	Coexistence Between SNMPv1/v2/3		
2578	SMv2		
2579	Textual Conventions for SMv2		
2580	Conformance Statements for SMv2		
2618	RADIUS Authentication MIB		
2665	Ethernet-like Interfaces MIB		
2674	Extended Bridge MIB		
2787	VRRP MIB		
2819	RMON MIB (groups 1, 2, 3, 9)		
2863	Interfaces MIB		
2865	RADIUS		
3273	RMON High Capacity MIB		
3416	SNMPv2		
3418	SNMP MIB		
3434	RMON High Capacity Alarm MIB		
3580	802.1X with RADIUS		
5060	PIM MIB		
ANSI/TIA-1057	LLDP-MED MIB		
draft-grant-tacacs-02	TACACS+		
draft-ietf-idr-bgp4-mib-06	BGP MIBv1		
IEEE 802.1AB	LLDP MIB		
IEEE 802.1AB	LLDP DOT1 MIB		
IEEE 802.1AB	LLDP DOT3 MIB		
ruzin-mstp-mib-02	MSTP MIB (traps)		
sFlow.org	sFlowv5		
sFlow.org	sFlowv5 MIB (version 1.3)		
FORCE10-BGP4-V2-MIB	Force10 BGP MIB (draft-ietf-idr-bgp4-mibv2-05)		
FORCE10-IF-EXTENSION-MIB			
FORCE10-LINKAGG-MIB			
FORCE10-COPY-CONFIG-MIB			
FORCE10-MON-MIB			
FORCE10-PRODUCTS-MIB			
FORCE10-SS-CHASSIS-MIB			
FORCE10-SMI			
FORCE10-SYSTEM-COMPONENT-MIB			
FORCE10-TC-MIB			
FORCE10-TRAP-ALARM-MIB			
FORCE10-FORWARDINGPLANE-STATS-MIB			

Regulatory compliance

Safety

UL/CSA 60950-1, Second Edition
 EN 60950-1, Second Edition
 IEC 60950-1, Second Edition Including All National Deviations and Group Differences
 EN 60825-1 Safety of Laser Products Part 1: Equipment Classification Requirements and User's Guide
 EN 60825-2 Safety of Laser Products Part 2: Safety of Optical Fibre Communication Systems
 FDA Regulation 21 CFR 1040.10 and 1040.11

Emissions

Australia/New Zealand: AS/NZS CISPR 22: 2009, Class A
 Canada: ICES-003, Issue-4, Class A
 Europe: EN 55022: 2006+A1:2007 (CISPR 22: 2006), Class A
 Japan: VCCI V3/2009 Class A
 USA: FCC CFR 47 Part 15, Subpart B:2009, Class A

Immunity

EN 300 386 V1.4.1:2008 EMC for Network Equipment
 EN 55024: 1998 + A1: 2001 + A2: 2003
 EN 61000-3-2: Harmonic Current Emissions
 EN 61000-3-3: Voltage Fluctuations and Flicker
 EN 61000-4-2: ESD
 EN 61000-4-3: Radiated Immunity
 EN 61000-4-4: EFT
 EN 61000-4-5: Surge
 EN 61000-4-6: Low Frequency Conducted Immunity

RoHS

All S-Series components are EU RoHS compliant.

Certifications

TAA (Trade Agreement Act) compliant models also available
 FIPS certified

