



# Dell PowerConnect M8024-k 10Gb Ethernet Switch

## For Dell M1000e Blade Enclosures

Expand the value of your blade investment with Dell™ PowerConnect™ M8024-k, delivering performance and scalability in a flexible package that are designed to meet the shifting demands of your business and data center as you transition to 10Gb Ethernet. Providing 10Gb Ethernet connectivity for up to sixteen M-Series blade servers equipped with the latest KR-based 10Gb network daughter cards (NDCs) or mezzanine cards, M8024-k simplifies deployment and management of M-Series blades within 10Gb Ethernet infrastructures. Not ready for 10Gb? No worries, as M8024-k supports 1Gb connections both to the server and to LAN, ensuring you'll be ready for 10Gb when the time comes. M8024-k's enhanced bandwidth, performance, and flexibility satisfy the changing demands of data centers embracing virtualization and other I/O-intensive technologies.

### Connect with the benefits of virtualization

With up to twenty-four total 10GbE ports, PowerConnect M8024-k meets the high bandwidth demands placed by multi-core CPUs and server virtualization. When combined with PowerEdge M710HD blade servers featuring 10Gb Network Daughter Cards, M8024-k provides end-to-end 10Gb Fabric A connectivity and leaves room for growth or other technologies in Fabrics B and C. Supporting connectivity to M-Series' KR-based 10Gb NICs and CNAs, M8024-k opens the door to cutting edge networking features such as NIC Partitioning (NPAR), SR-IOV, and iSCSI Offload.

### Simply deploy and manage

Deploy and manage 10Gb-based blade configurations simply and with minimal network admin involvement using M8024-k's default Simple Switch mode of operation, featuring port aggregation and auto-configuration when connecting to any external LAN. Alternatively, when operating in full switch mode, enjoy a shortened learning curve and seamless integration of M8024-k into existing Cisco® or other LANs using industry standard CLI (IS-CLI). These capabilities combined with enterprise-class QoS, Security, and management features, help ensure that M8024-k meets your in-chassis Ethernet switching needs both today and in the future.

### Flex and grow with FlexIO

Every PowerConnect M8024-k includes sixteen internal 1/10GbE ports, as well as four integrated external 1/10GbE SFP+ ports. To ensure room to grow and change with your business, each M8024-k also includes one FlexIO bay for modular uplinks that can be added or swapped as needed down the road. Choose from 4-port SFP+, 2-port 10GBASE-T, and 3-port CX-4 FlexIO Modules to expand aggregate (bi-directional) bandwidth by up to 80 Gigabit per second.

**M8024-k provides end-to-end 10Gb Fabric A connectivity and leaves room for growth or other technologies in Fabrics B and C.**

## Port attributes

- Up to 24 auto-sensing 10Gb Ethernet switching ports available
- 22 of this ports can be 1/10Gb
- 16 internal server 10Gb (KR) Ethernet ports with auto-negotiation capability to 1Gb Ethernet
- 4 external integrated 1/10Gb SFP+ Ethernet ports
- Up to 4 external ports via optional FlexIO plug-in module with flexible media choices:
  - 4-port SFP+ 10GbE module (10Gb only)
  - 3-port CX-4 10GbE copper module (10Gb only)
  - 2-port 10GBASE-T 10GbE copper module (1/10Gb)
- Auto-negotiation for speed, duplex mode and flow control
- Auto MDI/MDIX
- Port mirroring
- Flow-based port mirroring
- Broadcast storm control
- 10Gb (10GBASE-KR) adapters supported with M8024-k:
  - Brocade BR1741M-k mezzanine card
  - Broadcom 57712-k NDC
  - Intel X520-x/k mezzanine card
  - Future 10Gb adapters for M-Series blades
- 1Gb NICs (mezz card and LOM) are also supported

## Performance

- Switch Fabric Capacity 480 Gbps aggregate bandwidth
- Forwarding Rate 357 Mpps
- Up to 16K MAC Addresses
- 512MB of CPU SDRAM
- 32MB of Flash Memory

## Availability

- Spanning Tree (IEEE 802.1D) and Rapid Spanning Tree (IEEE 802.1w) with Fast Link Support
- Multiple spanning trees (IEEE 802.1s)
- Supports Virtual Redundant Routing Protocol (VRRP)

## Layer 3 routing performance

- Up to 128 RIP Routing Interfaces
- Up to 128 OSPF Routing Interfaces; up to 128 OSPF Areas; up to 128 Routing Interfaces per OSPF
- Area; up to 32 routes for ECMP Routing; up to 4 next hops per ECMP
- Up to 128 VLAN Routing Interfaces
- Up to 256 Multicast Forwarding Entries
- Up to 8K ARP entries; Up to 4K NDP entries

## VLAN

- VLAN support for tagging and port-based as per IEEE 802.1Q
- Double VLAN tagging (QinQ)
- Up to 1024 VLANs supported
- Dynamic VLAN with GVRP support

## Quality of Service

- Layer 2 Trusted Mode (IEEE 802.1p tagging)
- Layer 3 Trusted Mode (DSCP)
- Layer 4 Trusted Mode (TCP/UDP)
- Advanced Mode using Layer 2/3/4 flow-based Policies, including metering/rate limiting, marking and bandwidth guarantees; up to 100 ACLs can be used for QoS flow identification via Class-maps
- 8 Priority Queues per Port
- Adjustable Weighted-Round-Robin (WRR) and Strict Queue Scheduling
- Port-based QoS Services Mode
- Flow-based QoS Services Mode
- Priority Flow Control (PFC)
- iSCSI Optimization based on Link Layer Discovery Protocol (LLDP)

## Security options

- IEEE 802.1x based edge authentication — supports single and multiple host access, guest access, voice authorization, and

- Microsoft Active Directory
- Switch access password protection
- User-definable settings for enabling or disabling Web, SSH, Telnet, SSL management access
- Port-based MAC Address alert and lock-down
- Address filtering for management access via Telnet, HTTP, HTTPS/SSL, SSH and SNMP
- RADIUS and TACACS+ remote authentication for switch management access
- Up to 100 Access Control Lists (ACLs) supported; up to 127 rules per ACL; up to 28 Access Control Entries (ACEs) per ACL
- SSLv3 and SSHv2 encryption for switch management traffic
- Management access filtering via Management Access Profiles

## Other switching features

- Link Aggregation with support for up to 8 static aggregated links, 8 dynamic aggregated links per switch and up to 8 member ports per aggregated link; LACP support (IEEE 802.3ad)

## Management

- Default mode of operation is Simple Switch (port aggregator) mode to allow auto configuration of complex network settings
- User configurable to fully managed switch mode
- Web-based management interface
- Industry-standard CLI accessible via Telnet or Local Serial Port
- SNMPv1, SNMP v2c and SNMPv3 supported
- 4 RMON groups supported (history, statistics, alarms and events)
- TFTP transfers of firmware and configuration files
- Dual Firmware images
- Multiple Configuration file upload/download supported
- Statistics for error monitoring and performance optimization including port summary tables
- BootP/DHCP IP address management supported
- Syslog remote logging capabilities

## Chassis

- Single-wide I/O Module for M1000e blade enclosure
- 267 x 258 x 31mm (W x D x H)
- 10.5" x 10.2" x 1.2"
- Approximate weight: 2.7kg, 5.8 lbs

## Standards supported

- RFC 1213, 1215, 1286, 1442, 1451, 1492, 1493, 1573, 1643, 1757, 1907, 2011, 2012, 2013, 2233, 2618, 2665, 2666, 2674, 2737, 2819, 2863
- IEEE 802.1AB, 802.1D, 802.1Q, 802.1p, 802.1w, 802.1x, 802.2, 802.3, 802.3i, 802.3u, 802.3x, 802.3z, 802.ab, 802.3ac, 802.3ad, 802.3ae, 802.3ak

## Environmental

- Operating Temperature: 0° C to 45° C, Storage Temperature: -20° C to 70° C, Operating Relative Humidity: 10% to 90% non-condensing, Storage Relative Humidity: 10% to 95% non-condensing

## Regulatory and environmental compliance

- Regulatory Model: PCM8024-k, Product Safety, EMC and Environmental, Datasheets, Dell Regulatory Compliance Home Page, Dell and the Environment

© 2011 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge and PowerConnect are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to the products herein. The content provided is as-is and without expressed or implied warranties of any kind.

Learn more at [www.Dell.com/powerconnect](http://www.Dell.com/powerconnect)

